

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY AFFECT LIVER AND KIDNEYS.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 2 - Moderate (Life)

Flammability Rating: 2 - Moderate

Reactivity Rating: 1 - Slight

Contact Rating: 3 - Severe (Life)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES; CLASS B EXTINGUISHER

Storage Color Code: Red (Flammable)

Potential Health Effects

Inhalation:

Butyl alcohols have produced few cases of poisoning in industry because of their low volatility. Causes irritation to upper respiratory tract. Difficult breathing, coughing, headache, dizziness, and drowsiness may occur. May be absorbed into the bloodstream with symptoms similar to ingestion.

Ingestion:

May have narcotic effect. May cause abdominal pain, nausea, headache, dizziness, and diarrhea. Large doses may affect kidneys and liver. May affect hearing. Estimated mean lethal dose is 3 - 7 ounces.

Skin Contact:

An irritant to the skin, causing a loss of natural oils. Can be absorbed through skin with symptoms paralleling those from ingestion.

Eye Contact:

Vapors can be irritating, causing tearing and pain. Splashes cause inflammation and blurred vision.

Chronic Exposure:

Prolonged skin contact may cause drying and cracking of skin. Hearing loss has been reported in workers chronically exposed to butyl alcohol. May affect sense of balance, liver and kidneys.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point: 37C (99F) CC

Autoignition temperature: 343C (649F)

Flammable limits in air % by volume:

lel: 1.4; uel: 11.2

Flammable. Dangerous fire hazard when exposed to heat or flame.

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.

Fire Extinguishing Media:

Dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL):

100 ppm

-ACGIH Threshold Limit Value (TLV):

20 ppm (TWA)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a full facepiece respirator with organic vapor cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Clear, colorless solution.

Odor:

Strong characteristic, mildly alcoholic odor.

Solubility:

9 mL/100 mL water @ 25C

Specific Gravity:

0.81 @ 20C/4C

pH:

No information found.

% Volatiles by volume @ 21C (70F):

100

Boiling Point:

118C (244F)

Melting Point:

-89C (-128F)

Vapor Density (Air=1):

2.6

Vapor Pressure (mm Hg):

5 @ 20C (68F)

Evaporation Rate (BuAc=1):

0.46

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide may form when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Strong oxidizers, strong mineral acids, halogens, aluminum, chromium trioxide, alkali metals.

Conditions to Avoid:

Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Oral rat LD50: 790 mg/kg; inhalation rat LC50: 8000 ppm/4H; skin rabbit LD50: 3400 mg/kg; irritation, standard Draize, skin, rabbit, 20 mg/24H moderate; irritation, standard Draize, eye, rabbit, 2 mg/24H severe; investigated as a mutagen, reproductive effector.

Ingredient	Cancer Lists		
	NTP Carcinogen	Anticipated	IARC Category
Normal Butyl Alcohol	No	No	None

12. Ecological Information

Environmental Fate:

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material may evaporate to a moderate extent. When released to water, this material is expected to quickly evaporate. When released into water, this material is expected to readily biodegrade. This material has a log octanol-water partition coefficient of less than 3.0. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life between 1 and 10 days.

Environmental Toxicity:

The LC50/96-hour values for fish are over 100 mg/l. The EC50/48-hour values for daphnia are over 100 mg/l. This material is not expected to be toxic to aquatic life.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility.

Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations.

Dispose of container and unused contents - (D)2ccoons dnoc -10(w)2(i)-(t) federalstate(n 1 a)4lp

15. Regulatory Information

Che i c / Ingredient	Inventory St tus	P rt	TSCA	EC	p n	Austr / i
n Buty / A / coho /			Yes	Yes	Yes	Yes
Che i c / Ingredient	Inventory St tus	P rt 2	ore	C n d DSL	NDSL	Phi /
n Buty / A / coho /			Yes	Yes	No	Yes
Feder / Ingredient	St te	Intern tion /	Regu / tions	P rt	SARA 2	SARA /
n Buty / A / coho /					RQ TPQ	List Che i c / C tg
			No	No	Yes	No
Feder / Ingredient	St te	Intern tion /	Regu / tions	P rt 2	RCRA	TSCA
n Buty / A / coho /					2	d
					U	No
Che i c /	e pons Convention	No	TSCA 2	No	CDTA	Yes
SARA	2 Acute	Yes	Chronic	Yes	Fire	Yes
Re ctivity	No	Pure	Liquid		Pressure	No

Australian Hazchem Code: 3[Y]E

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products

Use only with adequate ventilation.
Avoid contact with eyes, skin and clothing.
Wash thoroughly after handling.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases call a physician.

Product Use:

Laboratory Reagent.

Revision Information:

MSDS Section(s) changed since last revision of document include: 3.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING